



Dimensions

Unit: ft-in (mm)

	A	B	C	D	E	F	G	H	I	J
ViO75-A	14'7"(4450)	15'5"(4700)	13'1"(4000)	22'11"(6980)	20'7"(6280)	9'6"(2890)	23'11"(7300)	15'4"(4680)	7'10"(2390)	8'11"(2715)
	K	L	M	N	O	P	Q	R	S	
ViO75-A	1'6"(460)	7'5"(2270)	1'6"(450)	1'3"(380)	7"('80)	2'6"(770)	1'10"(550)	1"(30)	3'8"(1130)	

Specifications

Model		VIO75-A	
Type		Cabin	
Operating weight	Rubber track	lbs (kg)	17530 (7950)
	Steel track	lbs (kg)	17640 (8000)
Engine	Type	Water-cooled 4 cyl. diesel	
	Model	4TNV98-XBV	
	Output	hp (kW)/RPM	58.2 (43.4) / 2000
Performance	Max. digging force, bucket/arm	lbs (kN)	11015/7284 (49.0 / 32.4)
	Traveling speed	MPH (km/h)	2.9 / 1.7 (4.7 / 2.7)
	Swing speed	RPM	10
	Boom swing angle, (L/R)	degrees	68 / 68
Ground contact pressure	Rubber track	PSI (kPa)	5.02 (34.6)
	Steel track	PSI (kPa)	5.06 (34.9)
Hydraulic system	Pump capacity	GPM	18.6 x 2 + 15.2 + 3.3
		(L/min)	(70.3 x 2 + 57.4 + 12.4)
	Main relief set pressure	PSI (MPa)	3553 (24.5)
Undercarriage	Track type	Rubber or steel	
Blade dimensions	Width x height	ft-in (mm)	7'5"x1'6" (2260x450)
Fuel tank capacity		Gals (L)	26.4 (100)

Hydraulic P.T.O.

Model	Output	VIO75-A		
		PSI(kPa)	GPM (L/min)	
Specifications			1900 RPM	1150 RPM
Combined flow, double actions		2986 (20595)	33.8 (127.7)	20.5 (77.3)